

Blast chiller room Metos BC200RB-PNR-CO2



Produktdata

Varenummer	4240753
Varenavn	Blast chiller room Metos BC200RB-PNR-CO2
Størrelse	990 × 1530 × 2040 mm
Vægt	550,000 kg
Kapasitet	85kg/+65...+3
Teknisk informasjon	400 V, 10 A, 0,795 kW, 3NPE, 50 Hz
Kjølemedie	CO2
Kjøleeffekt, W	6950

Beskrivelse

The Metos BC200RB is a blast chiller room designed for one GN2 / 1 trolley, with three powerful fans, carefully designed air circulation and precise control technology to guarantee a fast cooling result. The rooms also have a program for controlled defrosting of frozen products. PNR models are remote cooled models. The rooms do not have a separate floor element, which allows fast carriage filling without separate platform ramps.

A large 5-inch touch screen is mounted at the user's height on the hinge side of the door, where it is also protected from knocks. The user-friendly display allows quick recording of product-specific quick-freeze and defrost programs. Ready-made cooling and defrosting programs can be easily found using the pictograms. The device's USB port allows you to quickly download programs and other data to the machine's memory, as well as copy data from the machine's memory.

- blast chiller room without floor for trolleys
 - dimensioning for one GN 2/1-trolley
 - with remote cooling connection, machine not included
 - suitable for rapid cooling and defrosting
 - cooling capacity 85 kg (90min / + 70... + 3)
 - net internal dimensions of the room: (WxDxH) 785 x 940 x 1820 mm
 - electronic control and adjustable fan speed
 - large impact shields to protect the interior walls of the device
 - programming panel at an ergonomic height at the top of the door
 - product sensor with four measuring points
 - ergonomic, full-length opening handle
 - durable copper-aluminum evaporator
 - a tightly closing door and 80 mm thick polyurethane insulation improve energy efficiency
 - environmentally friendly polyurethane insulation
 - control of the cooling process by means of the internal temperature and surface temperature of the product
 - measurement and precise control of the smelting process by means of temperature and humidity
 - easy and fast to use with preset programs
 - pre-cooling function
 - the possibility to adjust the speeds of the evaporator fans during the cooling process
 - automatic transition to storage stage at the end of the quick-cooling process
 - stainless steel outer and inner lining
 - rounded inner corners make cleaning easier
 - cold power requirement 6950 W (at condensing temperature + 40 ° C and evaporation temperature -10 ° C)
 - the declared capacities (kg / h) are nominal values and are not achievable with all foods or under all conditions.
- ACCESSORIES (to be ordered separately):
- self-monitoring systems
 - refrigeration unit