

Blast chiller/freezer cabinet Metos MRBS-050-SAB Left



Produktdata

Varenummer	4240819
Varenavn	Blast chiller/freezer cabinet Metos MRBS-050-SAB Left
Størrelse	790 × 720 × 870 mm
Vægt	100,000 kg
Kapasitet	30kg/20kg/+90...+3/-18
Teknisk informasjon	230 V, 10 A, 1,046 kW, 1NPE, 50 Hz, 70 dB
Kjølemedie	R452A
Kjøleeffekt, W	814
Fordampningstemperatur	-25
Kondenseringstemperatur	+45

Beskrivelse

The Metos MRBS-050-SAB blast chilling and freezing cabinet quickly cools raw and cooked food. The food stays fresh and of high quality and, above all, clean. In professional kitchens, special attention must be paid to food safety. Our efficient blast chillers and freezers meet all HACCP requirements.

The Metos MRBS-050-SAB is equipped with cooling unit and 5" touch control on the door. The equipment is only 870mm high, so it fits under the table. The refrigerant in this model is R452A. There are ready-made programs for both chilling and freezing functions, from gentle to very



efficient. In addition to these, the user can store the user's own programs. The display shows the temperature and monitors the progress of the program. The appliance automatically switches to storage mode at the end of the quick cooling process. Inner and outer lining in easy-to-clean stainless steel. Rounded corners and a bottom plug make cleaning easier.

- 6 x GN 1/1-40 or 5 x GN 1/1-65
- height is only 870 mm, freezing cabinet fits under the table
- 5" touch control on the door, ergonomic
- save up to 99 programs with the core probe or time
- internal dimensions 670x335x400mm
- core probe is easy to be replaced by rotating a ring nut
- S/S condenser filter is easy to extract and clean, dishwasher safe
- air cooling
- stainless steel outside and inside internal coating with fully rounded corners
- Die-moulded and leakproof internal base
- Full-length flush ergonomic handle
- HCFC-free high-density polyurethane foam insulation (approx. 42kg/m³)
- Anti-condensation heating element situated on the body frame
- Magnetic seal on 4 sides of the door
- Left hinged door, which is not reversible
- Highly ventilated evaporator to ensure the cooling system's maximum efficiency
- USB connection for uploading new firmware release and downloading HACCP data
- chilling capacity 30kg/ +90...+3°C/90min, freezing capacity 20kg/+90...-18°C/240min
- stated capacities kg/h are nominal, and cannot be achieved with all food products and circumstances
- cooling power 814 W