

Blast chiller/freezer cabinet Metos MSB-050-RA Left



Produktdata

Varenummer	4240339
Varenavn	Blast chiller/freezer cabinet Metos MSB-050-RA Left
Størrelse	790 × 700 × 900 mm
Vægt	105,000 kg
Kapasitet	18kg/12kg/+90...+3/-18
Teknisk informasjon	230 V, 10 A, 1,046 kW, 1NPE, 50 Hz, 70 dB
Kjølemedie	R452A
Mængde kølemiddel, g/kg	1.000
Kjøleeffekt, W	814
Fordampningstemperat ur	-25
Kondenseringsteperatu r	+45

Beskrivelse

The Metos MSB-050-RA blast chilling and freezing cabinet quickly cools raw and cooked food. The food stays fresh and of high quality and, above all, clean. In professional kitchens, special attention must be paid to food safety.

The Metos MSB-050-RA is equipped with cooling unit and the refrigerant in this model is R452A. There are ready-made programs for both chilling and freezing functions, from gentle to

very efficient. In addition to these, the user can store the user's own programs. The appliance automatically switches to storage mode at the end of the quick cooling process. Inner and outer lining in easy-to-clean stainless steel. Rounded corners and a bottom plug make cleaning easier.

- capacity 5 x GN 1/1-65, rail distance 70mm
- cooling capacity 25 kg + 90 ° C ... + 3 ° C in 90 minutes, freezing capacity 15 kg + 90 ° C ... - 18 ° C in 240 minutes, stated capacities kg/h are nominal, and cannot be achieved with all food products and circumstances
- core probe
- programmes for both blast chilling and shock freezing
- when the program ends, the device automatically enters storage mode
- s/s exterior and interior
- cavity with central drain for discharge of washing water
- high-density polyurethane's insulation (aprox. 42 kg/m³), without CFC nor HCFC
- air cooling
- high performance copper-aluminum condenser
- left handed door, which is not reversible
- ergonomic handle across entire height of door and magnetic seals on all 4 sides of the door
- heating element in the door frame
- indirect blowing electronic fans, efficient but gentle on food
- manual defrosting device and condensate evaporation system without use of electrical energy
- control and command circuit board, easy to use
- compressor protected by thermic overload cut-out with automatic reset
- internal dimensions 670x335x400mm
- 80mm high feet